PRODUCT SPECIFICATION CHART

TASTIC CLASSIC RANGE

Product Name	Model Number	200 mm Fan	170 mm Fan	8W R63 Standard LED Globe	6W R63 LED Globe (Multi-option)	10W R80 LED Globe (Multi-option)	10W R80 Standard LED Globe	10W R80 LED Globe (Motion Sensor)	Back Draught Flaps	Ducted to Outside	Capacity Litres/ Sec	Capacity m^3/ hr	Half Heat Function	Cutout Dimensions (mm)	Max Ceiling Height	Max Height of Unit mm	Clearance Required above Unit (mm)	Minimum Ceiling Cavity Required (mm)	Watts (Fan in brackets)	Area Suitability with Shower (up to _m^2)
Vivid 2 IN 1 (No Fan)	11325	NO FAN				•	*	*			N/A	N/A		Template	2.4m	230	75	305	550	N/A
Vivid 3 IN 1	11323	•				•	*	*			86	310		Template	2.4m	230	75	305	590 (40)	6.46
Eco Vivid 3 IN 1	11344	•				•	*	*	•		74	266		Template	2.4m	290	75	365	590 (40)	5.54
Triumph 2 IN 1 (No Fan)	11317	NO FAN				*	•	*			N/A	N/A		Template	2.4m	230	75	305	550	N/A
Triumph 3 IN 1 (275W)	11311	•				*	•	*			78	279		Template	2.4m	230	75	305	590 (40)	5.81
Triumph 3 IN 1 (375W)	11312	•				*	•	*			78	279		Template	2.7m	230	75	305	790 (40)	5.81
Eco Triumph 3 IN 1	11341	•				*	•	*	•		72	257		Template	2.4m	290	75	365	590 (40)	5.35
Easy Duct Triumph	11511		•			*	•	*	•	•	58	210		Template	2.4m	215 (In-line fan)	15	230	590 (40)	4.38
Prime 3 IN 1	12309	•		*	•						86	310	•	262 x 262	2.7m	210	75	285	1140 (40)	6.46
Original 3 IN 1	11303	•		•	*						79	283	•	262 x 262	2.7m	210	75	285	1140 (40)	5.90
Paramount 3 IN 1	12310	•				•	*	*			107	385	•	330 x 330	2.7m	220	75	295	1140 (40)	8.02
Sensation 3 IN 1	12303	•				*	•	*			109	392	•	330 x 330	2.7m	220	75	295	1140 (40)	8.17
Eco Sensation 3 IN 1	12343	•				*	•	*	•		97	348	•	330 x 330	2.7m	220	90	310	1140 (40)	7.25
Easy Duct Sensation	12511		•			*	•	*	•	•	62	223	•	330 x 330	2.7m	215 (In-line fan)	15	230	1140 (40)	4.65
Silhouette 3 IN 1 (375W)	12301	•				*	•	*			113	407	•	330 x 330	3.3m	220	75	295	1540 (40)	8.48

TASTIC TRADE PACK

Product Name	Model Number	200 mm Fan	170 mm Fan	8W R63 Standard LED Globe	6W R63 LED Globe (Multi-option)	10W R80 LED Globe (Multi-option)	10W R80 Standard LED Globe	10W R80 LED Globe (Motion Sensor)	Back Draught Flaps	Ducted to Outside	Capacity Litres/ Sec	Capacity m^3/ hr	Half Heat Function	Cutout Dimensions (mm)	Max Ceiling Height	Max Height of Unit mm	Clearance Required above Unit (mm)	Minimum Ceiling Cavity Required (mm)	Watts (Fan in brackets)	Area Suitability with Shower (up to _m^2)
Vivid 3 IN 1 TRADE PACK	11463	•				•	*				86	310		Template	2.4m	230	75	305	590 (40)	6.46
Prime 3 IN 1 TRADE PACK	11454	•		*	•						86	310	•	262 x 262	2.7m	210	75	285	1140 (40)	6.46
Paramount 3 IN 1 TRADE PACK	11475	•				•	*				107	385	•	330 x 330	2.7m	220	75	295	1140 (40)	8.02

* Compatible

TASTIC ADVANCED RANGE

Product Name	Model Number	LED Light Wattage	LED Colour Temp Cool White 4000K	Heat Lamp Wattage	Fan Size (mm)	Minimum Ceiling Height (m)	Maximum Ceiling Height (m)	Maximum Height of Unit (mm)	Capacity Litres/ Sec	Capacity m^3/ hr	Clearance Required above Unit (mm)	Total Ceiling Cavity Required (mm)	Current Rating (Amps)	Watts (Fan in brackets)	Wall Switch Included	Ducting Included	Back Draft Flaps	Unit Dimensions (mm)	IPX4 Rated
Ovation 3 in 1	31511	3 x 7W GU Frosted	•	800	180	2.2	2.7	230	Up to 110	Up to 396	15	245	3.6	850(50)	•	•	•	358W x476Lx166D	

TASTIC PREMIUM RANGE

Product Name	Model Number	LED Light Wattage	LED Colour Temp Warm White 3000K	LED Colour Temp Cool White 4000K	Heat Lamp Wattage	Fan Size (mm)	Minimum Ceiling Height (m)	Maxi-mum Ceiling Height (m)	Maxi-mum Height of Unit mm	Clearance Required above Unit mm	Capacity (litres/ sec)	Capacity (m^3/h)	Total Ceiling Cavity Required mm	Current Rating (Amps)	Watts (Fan in brackets)	Wall Switch Included	Ducting Included	Back Draft Flaps	Unit Dimensions (mm)	IPX4 Rated
Luminate Single White	31411	25	•	•	800	170	2.2	2.7	230	15	133	480	245	3.6	875(75)	•	•	•	367Wx483Lx198D	
Luminate Single Silver	31412	25	•	•	800	170	2.2	2.7	230	15	133	480	245	3.6	875(75)	•	•	•	367Wx483Lx198D	
Luminate Dual White	32411	25	•	•	1600	170	2.2	3.3	230	15	133	480	245	7.0	1675(75)	•	•	•	367Wx733Lx198D	
Luminate Dual Silver	32412	25	•	•	1600	170	2.2	3.3	230	15	133	480	245	7.0	1675(75)	•	•	•	367Wx733Lx198D	
Luminate Vent White	35401	N/A			N/A	170	N/A	N/A	230	15	111	400	245	0.3	0(75)		•	•	367Wx243Lx210D	•
Luminate Vent Silver	35402	N/A			N/A	170	N/A	N/A	230	15	111	400	245	0.3	0(75)		•	•	367Wx243Lx210D	•
Luminate Vent & Light White	34401	17	•	•	N/A	170	N/A	N/A	230	15	111	400	245	0.4	90(75)	•	•	•	367Wx243Lx210D	•
Luminate Vent & Light Silver	34402	17	•	•	N/A	170	N/A	N/A	230	15	111	400	245	0.4	90(75)	•	•	•	367Wx243Lx210D	•
Luminate Heat White	36411	N/A			800	N/A	2.2	2.7	160	75	N/A	N/A	235	3	800(0)				367Wx326Lx160D	
Luminate Heat Silver	36412	N/A			800	N/A	2.2	2.7	160	75	N/A	N/A	235	3	800(0)				367Wx326Lx160D	
Neo Single White	31111	3x7W-GU10		•	800	170	2.2	2.7	230	15	96	346	245	3.6	875(75)	•	•	•	361Wx481Lx170H	
Neo Single Silver	31112	3x7W-GU10		•	800	170	2.2	2.7	230	15	96	346	245	3.6	875(75)	•	•	•	361Wx481Lx170H	
Neo Dual White	32111	3x7W-GU10		•	1600	170	2.2	3.3	230	15	96	346	245	7.0	1675(75)	•	•	•	361Wx735Lx170H	
Neo Dual Silver	32112	3x7W-GU10		•	1600	170	2.2	3.3	230	15	96	346	245	7.0	1675(75)	•	•	•	361Wx735Lx170H	
Neo Vent White	35101	N/A			N/A	170	N/A	N/A	230	15	104	375	245	0.3	0(75)		•	•	361Wx237Lx200H	•
Neo Vent Silver	35102	N/A			N/A	170	N/A	N/A	230	15	104	375	245	0.3	0(75)		•	•	361Wx237Lx200H	•
Neo Vent n Lite White	34101	3x7W-GU10		•	N/A	170	N/A	N/A	230	15	104	375	245	0.4	96(75)		•	•	361Wx237Lx200H	
Neo Vent n Lite Silver	34102	3x7W-GU10		•	N/A	170	N/A	N/A	230	15	104	375	245	0.4	96(75)		•	•	361Wx237Lx200H	
Neo Heat White	36111	N/A			800	N/A	2.2	2.7	160	75	N/A	N/A	235	3.3	800(0)				361Wx320Lx156H	
Neo Heat Silver	36112	N/A			800	N/A	2.2	2.7	160	75	N/A	N/A	235	3.3	800(0)				361Wx320Lx156H	

IXL VENTILATION RANGE

Product Name	Model Number	170 mm Fan	200 mm Fan	250 mm Fan	Light & Exhaust Fan	Back Draught Flaps	Ducted to Outside	Capacity (litres/ sec)	Capacity (m^3/h)	Area Suitability Room With Shower (m^2)	Light	Cutout Size (mm)	Clearance Required Above Unit (mm)	Watts	IP Rating
Ventflo 200mm	10330		•					86	310	6.46	N/A	240	180	25	
Ventflo 250mm	10331			•				149	538	11.21	N/A	290	180	35	
Eco Ventflo 200mm	10332		•			•		129	465	9.68	N/A	242	215	35	IPX2
Eco Ventflo 250mm	10333			•		•		173	624	13	N/A	295	260	45	IPX2
Ducted Ventflo Fan 200mm	10334		•			•	•	77	280	5.83	N/A	240	210	45	IP24
Ducted Ventflo Fan & Light 200mm	10336		•		•	•	•	77	280	5.83	12W LED Panel 4000K Cool White	240	210	45	IP24
Ducted Ventflo Fan 250mm	10337			•		•	•	100	360	7.50	N/A	295	242	60	IP24
Ducted Ventflo Fan & Light 250mm	10338			•	•	•	•	100	360	7.50	12W LED Panel 4000K Cool White	295	242	60	IP24
Ventflo Vent N Lite Deluxe	10363		•		•			92	321	6.68	2 X 42W Halogen (Incl)	262 x 262	285	124	
Ventflo Easy Duct Extraction	10380	•					•	55	198		N/A	160 dia.	230	40	