

Builder Project
Twin Shower Set



Versions:202506

Drawing



Specifications

Watermark License
WM-060093

Temperature Rating
Min 1˚C-Max 75˚C

Pressure Rating
Min 150kpa - Max 500kpa

Packaging Includes

1x Shower Arm
1x Shower Rail
1x Shower Head
1x Hand Shower (Built- In Check Valve)
1x 1.5m PVC Hose

Finish & SKU

● Matte Black
NR232105MB


*Dimensions are nominal measurements only.




1.Drill a φ6mm hole at the outlet vertical downward position in the recommended range.




2.Screw the adapter onto the outlet.
Push wall plug into drilled hole.
Fit lower mounting pillar in place with screw.Tighten firmly.




3.Screw shower rail into shower arm component. Tighten firmly.
Push 2 back plates onto shower arm component and lower mounting pillar.



4. Locate and push shower rail assembly onto wall adaptors.
Tighten grub screws firmly with allen key provided.
Slide the back plates against the wall/tile face properly.



5.Screw shower head to shower arm with care. (Note the rubber washer in the shower head.)



6.Please noted the rubber washer in the hand shower.
Connect shower rail and hand shower with hose.
TEST & CHECK FOR LEAKS.

Nero

Warranty Policy